Nozzle Type Vacuum Sealer



ETN series stainless steel vacuum sealer is engineered for heavy duty usage and smooth operation. Its control system is powered by PLC controller and Touch Panel Interface (HMI) for precise settings and user-friendly operations. The entire body is constructed with stainless steel to suite electronic & medical cleanroom standard and food industry requirements. Twin nozzles and high capacitity vacuum ejector pump create high flow of vacuum suction.

Standard Features:

- Suitable for clean room applicationHigh flow stainless steel retractable
- twin nozzles
- Clean, quiet, non-particle generating, 100% maintenance free air-driven vacuum ejector
- Easy set-up using only compressed air and a standard electrical outlet
- PLC controller
- Vacuum gauge
- Touch Panel Interface (HMI)
- Twin Nozzles with Changeable Pitch 2 Pitch Distance
- Foot pedal switch activated
- Built-in emergency stop push button
- Object / Finger anti-pinch safety system
- Fully stainless steel
- Bi-Active Impulse Sealing (Top & Bottom Heating)

Applications:

- Moisture resistance sealing
- Extend storage period for packed goods.
- Pouch Materials = Aluminum Foil, OPP Films, Nylon, HDPE, LDPE, Laminated Films

Model Selection:

- ETN-XX-L16 = Oil Lubricated Vacuum Pump
- ETN-XX-D16 = Dry Vacuum Pump

Model:	ETN-30	ETN-32
Seal Size:	(L) 30" x (W) 8mm	(L) 32" x (W) 8mm
Machine Dimension:	L30.5"x W20"x H13.5"	L32.5"x W20"x H13.5"
Power:	1Φ, AC 110V	10, AC 110V
Vacuum Flow:	9.40 cfm	9.40 cfm
Maximum Vacuum:	-26inHg	-26inHg
Air Requirement:	5CFM @ 87PSI	5CFM @ 87PSI
Model:	ETN-36	ETN-40
Seal Size:	(L) 36" x (W) 8mm	(L) 40" x (W) 8mm
Machine Dimension:	L36.5"x W20"x H13.5"	L40.5"x W20"x H13.5"
Power:	1Φ, AC 110V	10, AC 110V
Vacuum Flow:	9.40 cfm	9.40 cfm
Maximum Vacuum:	-26inHg	-26inHg
Air Requirement:	5CFM @ 87PSI	5CFM @ 87PSI

Note: Machine and specifications are subjected to change due to continuous improvement.

Contact Us : NASAVAC LLC 1150 SW Santa Fe Drive,Lees Summit, MO 64081,USA. Website: www.nasavac.com Email: sales@nasavac.com

Optional Upgrade:

- Stainless Steel Working Platform
- Standard Working Stand
- BUSCH Dry Vacuum Pump
- BUSCH Oil Lubricated Vacuum Pump
- Vertical Stand
- 10mm Sealing Width
- Other Sealing Length available
- Other voltage available (AC 220V)
- Liquid trapping kit





For more information, please contact local distributor :