

SINGLE CHAMBER VACUUM SEALER

NEPTUNE 28 (Front & Back Seal Bar)

NEPTUNE 28 - floor standing single chamber vacuum sealer has digital control, twin sealing bar. It is ideal for the packaging of several pouches per cycle of large sized products. The control system is powered by microcontroller with 10 programmable memory settings. The transparent glass lid assist in vacuum packaging process visualization. The optional soft air prevents damage to delicate products.







Features:

- Splash Proof, Heat Resistance & Soft Touch Control Panel
- Microcomputer Control System
- Powerful & Large Diameter Vacuum Valve (To Shorten Vacuum Time)
- Aluminum Alloy Sealing Bar (USA Standard)
- 10 sets Memory for Programmable Setting
- Fully Stainless Steel Fabrication
- Single Chamber


Optional Accessories:

Gas Flushing

Soft Air Sensor

Other Voltage Configuration

Chamber Diagram





Applications:

Packaging electronics, poultry, seafood, agricultural products, pickled foods, vegetarian foods, prepared foods, powder, spices, medical products and hardware parts.

Functions:

- Maintaining food's freshness and flavor, antiseptic, and mold resistant.
- Extend storage period for packed goods.
- Prevents electronic and hardware parts from rusting, oxidization and dampening.
- Suitable for clean room packaging (subjected to vacuum pump exhaust external installation, and type of vacuum pump)

SPECIFICATIONS

Vacuum Pump Capacity:

Chamber Depth: 6" or 9 %" Either one to select upon placing order (L) 33 1/2" x (W) 28 3/4" x (H) 34 1/4 " Machine Dimensions: 1Ф, 220V, 50Hz / 60Hz Power: 27 1/2" Sealing Length: Sealing Width: 3.5mm x 2 Lines Flat Heating Element

Note: Machine and specifications are subjected to change due to continuous improvement.



NASAVAC

20 m3/H, 1HP Oil Lubricated Rotary Vane Vacuum Pump

116 E 30TH Street, Kansas City, MO 64108, USA. Tel: +1 (816) 309-3134

Website: www.nasavac.com Email: info@nasavac.com



SINGLE CHAMBER VACUUM SEALER NEPTUNE 28S (Left & Right Seal Bar)

NEPTUNE 28S - floor standing single chamber vacuum sealer has digital control, twin sealing bar. It is ideal for the packaging of several pouches per cycle of large sized products. The control system is powered by microcontroller with 10 programmable memory settings. The transparent glass lid assist in vacuum packaging process visualization. The optional soft air prevents damage to delicate products.







Features:

- Splash Proof, Heat Resistance & Soft Touch Control Panel
- Microcomputer Control System
- Powerful & Large Diameter Vacuum Valve (To Shorten Vacuum Time)
- Aluminum Alloy Sealing Bar (USA Standard)
- 10 sets Memory for Programmable Setting
- Fully Stainless Steel Fabrication
- Single Chamber


Optional Accessories:

Gas Flushing

Soft Air Sensor

Other Voltage Configuration

Chamber Diagram





Applications:

Packaging electronics, poultry, seafood, agricultural products, pickled foods, vegetarian foods, prepared foods, powder, spices, medical products and hardware parts.

Functions:

- Maintaining food's freshness and flavor, antiseptic, and mold resistant.
- Extend storage period for packed goods.
- Prevents electronic and hardware parts from rusting, oxidization and dampening.
- Suitable for clean room packaging (subjected to vacuum pump exhaust external installation, and type of vacuum pump)

SPECIFICATIONS

Chamber Depth: 6" or 9 %" Either one to select upon placing order Machine Dimensions: (L) 33 ½" x (W) 28 ¾" x (H) 34 ¼ "

1Ф, 220V, 50Hz / 60Hz Power:

21 1/4" Sealing Length:

Sealing Width: 3.5mm x 2 Lines Flat Heating Element

Vacuum Pump Capacity: 20 m3/H, 1HP Oil Lubricated Rotary Vane Vacuum Pump

Note: Machine and specifications are subjected to change due to continuous improvement.



NASAVAC

116 E 30TH Street, Kansas City, MO 64108, USA. Tel: +1 (816) 309-3134

Website: www.nasavac.com Email: info@nasavac.com



SINGLE CHAMBER VACUUM SEALER

NEPTUNE 28L (L-Shape Seal Bar Configuration)

NEPTUNE 28L - versatile vacuum sealer with L-shape seal bar configuration, mobility, and heavy duty usage. It is ideal for the packaging of several pouches per cycle of large sized products. The control system is powered by microcontroller with 10 programmable memory settings. The transparent glass lid assist in vacuum packaging process visualization. The optional soft air prevents damage to delicate products.







Features:

- Splash Proof, Heat Resistance & Soft Touch Control Panel
- Microcomputer Control System
- Powerful & Large Diameter Vacuum Valve (To Shorten Vacuum Time)
- Aluminum Alloy Sealing Bar (USA Standard)
- 10 sets Memory for Programmable Setting
- Fully Stainless Steel Fabrication
- Single Chamber


Optional Accessories:

Gas Flushing

Soft Air Sensor

Other Voltage Configuration

Chamber Diagram





Applications:

Packaging electronics, poultry, seafood, agricultural products, pickled foods, vegetarian foods, prepared foods, powder, spices, medical products and hardware parts.

Functions:

Sealing Length:

- Maintaining food's freshness and flavor, antiseptic, and mold resistant.
- Extend storage period for packed goods.
- Prevents electronic and hardware parts from rusting, oxidization and dampening.
- Suitable for clean room packaging (subjected to vacuum pump exhaust external installation, and type of vacuum pump)

SPECIFICATIONS

Chamber Depth: 6" or 9 ¾" Either one to select upon placing order

Machine Dimensions: (L) 33 ½" x (W) 28 ¾" x (H) 34 ¼ "

Power: 1Φ, 220V, 50Hz / 60Hz

Sealing Width: 3.5mm x 2 Lines Flat Heating Element

Vacuum Pump Capacity: 20 m3/H, 1HP Oil Lubricated Rotary Vane Vacuum Pump

Note: Machine and specifications are subjected to change due to continuous improvement.

1 x 21 ¼" and 1 x 25 ½"



NASAVAC LLC

116 E 30TH Street, Kansas City, MO 64108, USA. Tel: +1 (816) 309-3134

Website: www.nasavac.com Email: info@nasavac.com